

Job No.: SZAIE190929003

Standard: (RE)EN55032\_class B\_3m

Test item: Radiation Test

Temp.( C)/Hum.(%) 22.8 / 49 %

EUT: EBF6ULL S1 Mini

Mode: ON

Model: EBF6ULL S1 Mini

Polarization: Vertical

Power Source: AC 230V/50Hz


Date: 2019/10/22

Time: 10:02:49

Engineer Signature: John Fang

Distance: 3m

Note: Test Sample No.:1-1-1



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	68.8721	43.26	-20.98	22.28	40.00	-17.72	peak			
2	97.4560	38.83	-16.71	22.12	40.00	-17.88	peak			
3	162.6106	44.89	-20.28	24.61	40.00	-15.39	peak			
4	394.8544	45.72	-14.37	31.35	47.00	-15.65	peak			
5	441.7425	47.55	-13.58	33.97	47.00	-13.03	peak			
6	766.0571	45.34	-8.43	36.91	47.00	-10.09	peak			

Job No.: SZAIE190929003

Standard: (RE)EN55032\_class B\_3m

Test item: Radiation Test

Temp.( C)/Hum.(%) 22.8 / 49 %

EUT: EBF6ULL S1 Mini

Mode: ON

Model: EBF6ULL S1 Mini

Polarization: Horizontal

Power Source: AC 230V/50Hz


Date: 2019/10/22

Time: 10:05:37

Engineer Signature: John Fang

Distance: 3m

Note: Test Sample No.:1-1-1



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	98.4866	40.05	-22.64	17.41	40.00	-22.59	peak			
2	115.7256	44.67	-24.29	20.38	40.00	-19.62	peak			
3	162.6106	55.34	-24.02	31.32	40.00	-8.68	peak			
4	301.4224	52.07	-19.53	32.54	47.00	-14.46	peak			
5	394.8545	51.33	-15.37	35.96	47.00	-11.04	peak			
6	441.7426	50.11	-14.50	35.61	47.00	-11.39	peak			